The state of the s

	_
	1
•	1

Please type a plus sign (+) inside this box→

→	+

PTO/SB/05 (08-00) (modified)

Approved for use through 9/30/2001, OMB 0651-0032

UTILITY PATENT APPLICATION TRANSMITTAL

(only for new nonprovisional applications under 37 CFR 1.53(b))

Patent and Trademark Off	ice: U.S. DEPARTMENT OF COMMER(
Attorney Docket Number	2926
First Named Inventor	Andrew Wolfe
Title	A Superscalar 3D Graphics Engine
Express Mail Label No.	EL550795041US

	37 CFR 1.53(b))	Express	Mail Label No.	EL5507950	41US		
API	PLICATION ELEMENTS		ACCOMPANY			N PARTS	
	nsmittal Form (in duplicate)	7.					
	it claims small entity status. CFR 1.27	8.		of Priority D			iority
Specifica	ation Total Pages 32	7		,			ဥ
Description Cross Re Statemer Backgrou Brief Sun Brief Des Claim or Claim o	gement set forth below) ve Title of the Invention eference(s) to Related Case(s) nt Regarding Fed sponsored R & D und of the Invention nmary of the Invention ccription of the Drawing(s) Description Claims of the Disclosure (s) (35 U.S.C. 113) Total Sheets 8	9. 10. 11. 12. 13. 14. 15. 16.	Preliminary Ar	ppies of IDS o			
6. Application	n Data Sheet. See 37 CFR 1.76		ADDDECC	. TO:			
			ADDRESS				
				ent Applicati sioner for Pa			
				ton, D.C. 20			
Continuation Prior application For CONTINUATION C Box 5b, is considered a	on 🔲 Divisional 🔲 Continuation-in-p	ure of the pr	requisite information be of prior application Group/Art Unition application, from what is application and from the submitted appropriate in the submitted appropr	elow and in a p No: t: ich an oath or	reliminary a		
☐ Customer Nu			mer No. or	Or 🗌	Corres	spondence	
	Attac	ch bar cod	le label here)	٠. ي		ss below	
NAME	John R. Carr, Fenwick & West L	LP					
ADDRESS	Two Palo Alto Square						
CITY	Palo Alto	STATE	CA	ZIP	CODE	94306	
COUNTRY	U.S.A. TELEPHON	E (415)	875-2431	FAX		281-1350	
Name (Print/Type)	John R. Carr		Registration No. (Attorney/Agent		42,390	
Signature	John Car			Date	111	11.120	-روسازر
		***		AS	000/0000	0/SF/5034038.	.1

ded)

+

PTO/SB/17 (10-00)(modified)
Approved for use through 09/29/01, OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

0002/PTO(modified)	
Rev. 10/2000	

U.S. Department of Commerce Patent and Trademark Office

FEE TRANSMITTAL

TOTAL AMOUNT OF PAYMENT

Subtotal (1) + Subtotal (2) + Subtotal (3) = (\$) 1,156

Complete if Known						
Application Number	Please assign					
Filing Date	November 16, 2000					
First Named Inventor	Andrew Wolfe					
Group Art Unit	Unknown					
Examiner Name	Unknown					
Attorney Docket Number	2926					

	METHOD O	F PAYMENT			FEE CA	ALCULATION (continu	ued)	
1. The Co	mmissioner is l	hereby author	rized to:	3. ADDITIONA				
lпa	N. are			Large Entity	Small Entity			
	Charge the indicate nentioned deposit a	ed fees to the belo account.	ow	Fee Code/Fee	Fee Code/Fee	Fee Description		Fee Due
	harge any addition	nal foo required u	Indox 27	105/ \$130	205/ \$65	Surcharge - late filing fee of	r oath	
, c	FR 1.16 - 1.21 or on the below mention	credit any over pa	ayments	127/\$50	227/ \$25	Surcharge-late provisional	filing fee or cover sheet	
	pplicant claims sm			147/ \$2,520	147/ \$2,520	For filing a request for reex	amination	
· s	ee 37 CFR 1.27	rain officially oldered		115/ \$110	215/ \$55	Extension for response with	nin first month [†]	
ŀ				116/\$390	216/ \$195	Extension for response with	nin second month [†]	
Deposit Acc	count Number: 19 count Name: FEN	9-2555 NWICK & WEST	LLP	117/\$890	217/ \$445	Extension for response with	nin third month [†]	
. 2722	Copy of this auth			118/ \$1,390	218/ \$695	Extension for response with	nin fourth month [†]	
l "D	Payment Enclos			128/ \$1,890	228/ \$945	Extension for response with	nin fifth month [†]	
isais.	☑ Check ☐ C	redit Card	Other	119/ \$310	219/ \$155	Notice of Appeal		
1. FILING	FEE Small Entity	(fees effective 10	0/01/2000) Fee	141/\$1,240	241/ \$620	Petition to revive unintentio application	nally abandoned	
Fee Code/Fee	Fee Code/Fee	Description	Due	142/ \$1,240	242/ \$620	Utility Issue Fee (Or Reissu	e)	
101/\$710	201/ \$355	Utility Filing	710	143/ \$440	243/ \$220	Design Issue Fee		
106/ \$320	206/ \$160	Design Filing		122/\$130	122/\$130	Petitions to the Commission	ner	
108/ \$710	208/ \$355	Reissue		126/ \$180	126/ \$180	Submission of Information I	Disclosure Statement	
114/ \$:150	214/\$75			179/\$710	279/\$355	Request for Continued Exa	mination (RCE)	
! # "	214/\$15	Provisional Filing		581/ \$40	581/ \$40	Recording each patent assi		
2 pund 2 pund 2 pund 2 pund	SUBTOTA	L (1) (\$) 7	'10	440/0740		(times number of properties)	
2. CLAIMS	3			146/\$710	246/ \$355	Filing a submission after fin (37 CFR 1.129(a))	al rejection	
Large Entity Fee Code/Fee	Small Entity Fee Code/Fee	Fee Descripti	ion	149/\$710	249/ \$355	For each additional inventio (37 CFR 1.129(b))	n to be examined	
103/ \$18	203/\$9	Claims in exc	cess of 20					
102/ \$80	202/ \$40	Independent of in excess of 3			Other fee (specify): Other fee (specify):	37 CFR 1.20(d) Termina	al disclaimer fee	
104/ \$270	204/\$135	Multiple depe	endent claim		27	SIII	BTOTAL (3) (\$)	
109/ \$80	209/ \$40	Reissue inder	nandant	(0.1.4)			3101AL (3) (4)	
•	200/440	claims over or		(Col. 1) No. of For Existing	(Col. 2) Highest			Fee
110/ \$18	210/ \$9	Reissue claim		Claims	Previou Paid For		Fee	Due
•		of 20 and over patent	er onginal	TOTAL 27	minus* 20 or 0 minus* 3 or 0	= 7	x 18 =	126
					entation of multiple depend		x 80 = =	320
				* Subtract the gre	ater number of Col. 2	S	UBTOTAL (2) (\$)	446
SUBMITTED	RY			** If the difference	between Col. 1 and Col. 2	2 is less than zero, then enter	"0" in Col. 3	
Typed or Prin		ohn R. Carr				Complete (if ap	·	
Signature		olu (Date	42,390	
		A COSC (eu				11-16-2	000

A Superscalar 3D Graphics Engine

Inventor: Andrew Wolfe

Field of the Invention

The invention relates to 3D graphics systems. More specifically, the invention relates to an architecture for parallel processing of graphics primitives which allows the concurrent execution of multiple graphics primitives while maintaining exact sequential semantics.

Background of the Invention

Since the widespread introduction of graphical user interfaces in computers more than 15 years ago, special-purpose graphics accelerators have been an integral component of desktop computer systems. Recently, 3D applications such as computer gaming, CAD, and visualization applications have been pushing high-performance 3D acceleration from specialty work-stations into mainstream PCs. The demand for increased 3D performance is currently insatiable. Single-chip 3D accelerators today are 50 times faster than those available 3-4 years ago. Each generation substantially improves the quality of the images and yet another factor of 100 still would not produce truly realistic scenes.

Like all computing systems, in order to achieve such rapid increases in performance, it is necessary to improve the microarchitecture of each generation to increasingly take advantage of parallelism. Over the past few years, 3D graphics engines have moved from 32 to 64 to 128-bit memory buses in much the same way that microprocessors grew from 4 to 8 to 16 and eventually to 64 bit bus lines. However, this advancement in 3D graphics engines has

diminishing returns, especially as applications move toward a larger number of primitives for each scene to be displayed.

Current high-performance microprocessors all use instruction-level parallelism (ILP) to further increase performance. ILP exploits information about dependences between instructions to allow parallel execution of multiple instructions while maintaining the execution semantics of a sequential program. Many different ILP mechanisms can be effectively employed to improve performance, however dynamically scheduled, out-of-order, superscalar microprocessors are the commercially dominant microarchitecture at the present time.

This invention includes an approach for using dynamically scheduled, out-of-order, superscalar principles for increasing the available parallelism in a 3D graphics engine while maintaining sequential execution semantics. In the abstract, it would seem that graphics, and particularly 3D graphics, is a massively parallel application that would not need ILP technology for high performance. In fact, in many simple graphics applications, it would be possible to render each pixel independently; however, in practice, graphics applications have very similar characteristics to traditional sequential programs. Standard APIs like Direct3D or OpenGL are used to create graphics applications. These are translated via software drivers to a sequence of graphics primitives to be rendered by a graphics engine that consists of some combination of additional hardware and software. The programming model assumes that these primitives will be executed sequentially and atomically, in much the same manner that it is assumed that instructions in a traditional sequential ISA are executed.

Typically, 3D graphics applications will allow blocks of frame buffer memory to be directly read or written by the main processor. This requires that precise frame buffer state be available whenever a direct access executes. This creates a dependence between previous primitives and a direct read or subsequent primitives and a direct write. As in general-purpose computing systems, it is possible to build massively parallel systems that provide excellent performance on a limited set of applications that have been programmed with parallel execution in mind. However, in order to be compatible with a large existing base of software using widely accepted programming interfaces and programming styles, it is necessary to detect the dependences between graphics primitives, extract independent primitives from the instruction stream, and execute them concurrently. Therefore, in order to implement a parallel system for executing this sequence of primitives, the semantics of sequential execution must be maintained. More particularly, several factors cause dependences between graphics primitives which that can prevent concurrent or parallel execution of primitives in a 3D graphics engine.

Z-buffering

Realistic 3D graphics usually include hidden surface removal. More specifically, objects that are behind other objects from the perspective of the viewer should not be visible in the final image. Typically, a Z-buffer is used to implement hidden-surface removal. The Z-buffer stores the distance from the viewpoint to a currently drawn pixel so that when drawing a new pixel, it can be determined if the new pixel is in front of or behind the currently drawn pixel. A well-implemented Z-buffering algorithm should produce the same result even if the triangles are drawn in a different order. However, if the primitives are executed concurrently, then two triangles may be drawn concurrently. If each primitive attempts to concurrently read the same Z-buffer value, modify it, and then write the new value to the Z-buffer using common read and write operations, incorrect results can be produced. A special type of dependence thus

exists between any two primitives that must access the same Z-buffer value.

Although they can execute in either order, there is currently no known process for executing these primitives concurrently.

Alpha-blending

Alpha-blending is an operation that uses a transparency value (alpha) to permit some portion of an occluded object to be visible through a foreground object. Unfortunately, the primitives that execute alpha-blending operations to make objects appear transparent must be executed in order. The foreground and the background must be executed in order to make the transparent effect appear correct on the image. Accordingly, if the 3D graphics engine does not maintain the semantics of the sequence in which primitives are executed, the image will be incorrect.

Dynamic textures, procedural textures, environment mapping

In another feature of realistic 3D graphics, an image (called a texture) can be mapped onto another image; for example, it may be part of the image to have objects reflected off of water displayed in the image. Often these textures have limited life-times. Procedural textures are created on-the-fly by program code. Dynamic textures are loaded into the graphics system memory space from some backing store for a limited time. Environment mapping is a technique for reflections where the 3D objects which is to be reflected is drawn and then copied as an image to be mapped onto a reflective surface. In each of these cases, there is a dependence between the primitives that create the texture and the primitives that render the reflective surface or polygon upon which the texture is projected. Once again, if the 3D graphics engine does not maintain the semantics of the sequence in which primitives are executed, the image will be incorrect.

2D BLITs

Often in 3D graphics, it is advantageous to be able to mix 2D block copy and drawing operations with 3D rendering. If overlapping 2D objects are read or written out of order, the resulting image is incorrect.

Direct Frame Buffer Access

Common graphics API's allow blocks of frame buffer memory to be directly read from or written to at the same time by the processor. This requires that the precise state of the frame buffer be available and known whenever an access to the frame buffer memory executes. This creates a dependence between any previously executed primitives and a direct read or any future executed primitives and a direct write.

Generally, a 3D application creates a series of frames. A 3D graphics engine then identifies each of the objects in a frame and breaks the surface of the object down into a collection of triangles for processing (typically the processing and drawings of the pixels within these triangles are represented by a serious of executable instructions which are referred to as primitives which are processed individually). Each triangle or primitive is specified by three vertices in a 3D space, one or more surface normals, and a description of how to draw the triangle's surface, i.e. texturing, alpha blending parameters, etc. Accordingly, from the point of view of a 3D graphics engine, a frame consists of a collection of triangles or primitives which are all processed and executed separately thereby rendering the entire frame or image. The 3D graphics engine is responsible for processing each triangle or primitive and converting them each into pixels, which when displayed render the entire 3D frame.

FIG. 1 illustrates a block diagram which shows a prior art 3D processing pipeline resident in a prior art 3D graphics engine. Generally, the graphics engine identifies the triangular coordinates for each primitive within the shared world space of the entire image, applies lighting to the triangles or primitives, transforms each triangle or primitive from the 3D space used by the application into 2D screen coordinates, and draws the appropriate pixels into the frame buffer (applying any shading, z-buffering, alpha bending etc.).

Referring now to FIG. 1, and more specifically, the first stage in the pipeline is the world transform stage 105, in which the graphics engine converts the vertices and normals of the triangle from the real world object space, which may be different for each object in the scene, to the shared world space, which is the space shared by all of the objects to be rendered in the entire scene. This transform consists of a matrix-vector multiplication for each vertex and each normal. In the second stage of the pipeline, the lighting stage 110, the graphics engine takes the triangle's color and surface normal(s) and computes the effect of one or more light sources. The result is a color at each vertex. At the next stage in the pipeline, the view transform stage 115, the graphics engine converts the vertices from world space to a camera space, with the viewer (or camera) at the center or origin and all vertices then mapped relative from that origin. Additionally, in the view transform stage 115, the graphics engine applies a matrix-vector multiplication to each vertex calculated for the camera space.

As further shown in FIG. 1, the next stage in the pipeline is the projection transform stage 120. At the projection transform stage 120, the graphics engine maps the vertices from the camera space to the actual view space. This includes the perspective transformation from 3D to 2D. Accordingly, at this point in the pipeline, the vertices are effectively two-dimensional to

which perspective effects (i.e. depth foreshortening) have been applied. Accordingly, the third (z) coordinate is only needed to indicate the relative front-to-back ordering of the vertices when the objects are rendered or drawn within the view space. Like the other two transform stages in the pipeline, the projection transform stage requires the application of a matrix-vector multiplication per each vertex. In the clipping stage 125, the graphics engine clips the triangles or primitives to that the fit within the view space. Accordingly, triangles or primitives which lie entirely off the side of the screen or behind the viewer are removed. Meanwhile, triangles or primitives which are only partially out of bounds are trimmed. This generally requires splitting the resulting polygon into additional multiple triangles or primitives and processing each one of these additional triangles or primitives separately. Finally, in the rasterization stage 130, the graphics engine converts those triangle to be displayed within the view space into pixels and computes the color value to be displayed at each pixel. This includes visible-surface determination (dropping pixels which are obscured by a triangle closer to the viewer), texture mapping, and alpha blending (transparency effects).

FIG. 2 further illustrates how a prior art rasterizer stage 130 in a 3D graphics engine operates. First, the rasterizer calculates the centers for each pixel in the triangle or primitive and assigns x and y values to these centers. The rasterizer stage then converts each triangle or primitive into a series of horizontal spans, with one span generated for each integer y value that falls inside the triangle. For each horizontal span, the rasterizer computes the two endpoints, i.e. the points where the horizontal span crosses the edges or boundaries of the triangle or primitive. The rasterizer will also interpolate color values and perspective-corrected texture coordinates for the endpoints. Next, the rasterizer generates the series of pixels along the span, again interpolating color and texture coordinates for each pixel between the two endpoints of

the horizontal span. Several operations are then performed at each pixel. First each pixel has its z (depth) value compared to the z (depth) value for the currently displayed pixel in the same location. The currently displayed pixel has its z (depth) value stored in a z buffer. If the comparison indicates that this new pixel is behind the old one, the new pixel is discarded. If the comparison indicates that this new pixel is in front of the old pixel then the z test succeeds and the new pixel color is computed. This can include texture mapping and alpha blending. Accordingly, prior art 3D graphics are computed serially because each z (depth) value must be compared to the previously displayed z (depth) value.

Generally, a prior art 3D graphics engine will serially perform these steps on each triangle or primitive one at a time, such that the triangles or primitives are processed in an orderly fashion one after the other in series. One reason this is done is to avoid any dependencies which may occur between the primitives or triangles as they are each executed. As explained earlier, as each primitive is executed for processing, the z values for each pixel location in the triangle or primitive is compared with the z value previously displayed in that same location on the two dimensional screen in order to determine whether the new pixel should overwrite (appear in front of) the old value or be ignored (appear behind). If the triangles are not executed in order, then the z value test results will be faulty.

However, the present invention is directed toward a method, apparatus and computer program product for parallel execution of primitives in 3D graphics engines. It includes detection and preservation of dependences between graphics primitives. Accordingly, the present invention has the ability to execute multiple independent primitives concurrently while preserving their ordering because the architecture of the graphics engine for the present

invention further provides concurrent resources for parallel execution. In a first preferred embodiment, primitives are executed in parallel using an in-order dispatch unit capable of detecting dependencies between primitives. In a second preferred embodiment, an out-of-order dispatch unit is used such that not only are primitives executed concurrently; but, the primitives may be executed in any order when dependencies are detected.

Brief Description of the Drawings

FIG. 1 illustrates a block diagram which shows a prior art 3D processing pipeline resident in a prior art 3D graphics engine;

FIG. 2 illustrates further how a prior art rasterizer stage 130 in a 3D graphics engine operates;

FIGs 3a-b illustrate how a first preferred embodiment of a 3D graphics engine uses an in-order dispatch mechanism which dispatches each primitive from the head of the input list, in order, as an accelerator becomes available;

FIG 4a-c illustrate the basic concepts used in the process of 3D graphics in accordance with a second preferred embodiment of the present invention which uses an out-of order dispatch mechanism;

FIG 5 illustrates a functional block diagram showing an out-of-order dispatch mechanism in accordance with a preferred embodiment of the present invention;

FIGs. 6a and 6b illustrate the process executed when processing graphics primitives and using either an in-order or an out-of-order dispatch mechanism in accordance with a preferred embodiment of the present invention; and

FIG. 7 illustrates a block diagram which shows a preferred embodiment of the hardware used to compute dependency vectors for each primitive.

Detailed Description of Preferred Embodiments

In the present invention, an out-of-order dispatch 3D graphics engine detects dependences and maintains sequential semantics at the rasterizer stage to extract ILP from the graphics primitive stream. Multiple rasterization engines are used to provide execution resources for the graphics primitives such that multiple graphics triangles or primitives may be executed at the same time. Since primitives can have long execution times, from several cycles to several hundred thousand cycles, it is not very important to dispatch more than one primitive per cycle, although it is possible to do so. However, it is important to have many primitives executing concurrently. Also, since the primitives do many memory accesses and require an indeterminate number of cycles to execute, it is best to have the rasterization engines run independently. Accordingly, in a preferred embodiment of the present invention, the graphics engine operates in a multiple instruction/multiple data MIMD fashion, which means the graphics engine is capable of processing multiple primitives at the same time.

In Order Dispatch Unit

FIGs 3a-b illustrate how a preferred embodiment of a graphics engine uses an in-order dispatch system in order to dispatch primitives for concurrent execution by two or more graphics accelerators in accordance with the present invention. In this embodiment, each primitive is ranked in order in an input list and is dispatched from the head of the input list, in order, as an accelerator becomes available. As shown in FIG 3a, a 3D image is broken into a

number of triangles or primitives, i.e. each triangle is a primitive which must be processed for display by the graphics engine. In a typical prior art 3D graphics engine, the coordinates for the vertices of the primitives are stored in a queue for serial execution/processing by the 3D graphics engine. The primitives are executed in order serially one at a time from the queue. However, in the present invention more than one primitive may be executed at a time so the queue has what is referred to as an in-order dispatch system.

Assume in the preferred embodiment illustrated that there are two graphics accelerators capable of executing two graphics primitives in parallel such that two primitives may be dispatched to the two simultaneously executing accelerators/rasterizers in the 3D graphics engine. Accordingly, FIG. 3b shows primitives 1 and 2 being executed while primitives 3, 4 and 5 remain in the queue. When using an in-order dispatch unit in accordance with a preferred embodiment of the present invention, each subsequent primitive is tested against currently executing primitives in order to detect any dependencies. Accordingly, in our example, primitive 3 will be tested against primitives 1 and 2 for dependencies. Since primitive 3 overlaps primitives 1 and 2, primitive 3 cannot be executed until primitives 1 and 2 are both complete. This is because triangles associated with primitives 1 and 2 are both overlapped by the triangle represented by primitive 3. Thus, even if primitive 1 completes before primitive 2, primitive 3 cannot begin processing/execution until primitive 2 has completed. In this embodiment, the graphics engine cannot execute primitive 4 because it includes an in-order dispatch system which does not permit out of order execution and processing of the primitives. Accordingly, the in-order dispatch system prevents the next primitive in the list from executing until all previous primitives that overlap that primitive have been completed and all primitives which are in the queue before that primitive have executed. This allows for parallel processing

and execuion of primitives while preserving the ordering and integrity of the primitives thereby insuring that the final graphic is properly drawn.

Out of Order Dispatch

FIG 4a-c illustrate how a preferred embodiment of a graphics engine uses an out-of-order dispatch system in order to dispatch primitives for concurrent execution by two or more graphics accelerators in accordance with the present invention. As shown in FIG 4a, a 3D image is broken into a number of triangles, each triangle represented by a primitive. The primitives are stored in a queue for execution/processing by the 3D graphics engine.

Assume in the preferred embodiment illustrated that there are two graphics accelerators capable of executing two graphics primitives in parallel such that two primitives may be dispatched to the two simultaneously executing accelerators/rasterizers in the 3D graphics engine. However, unlike the preferred embodiment which utilizes an in-order dispatch unit, in the embodiment which utilizes an out of order dispatch unit, the primitives may be executed out-of-order since the queue has an out-of-order dispatch system.

Accordingly, once again assume in the example illustrated that two primitives may be dispatched to two simultaneously executing accelerators/rasterizers in the 3D graphics engine. FIG. 4b shows primitives 1 and 2 being executed while primitives 3, 4 and 5 remain in the queue. When using the out-of-order dispatch unit in accordance with a preferred embodiment of the present invention, each subsequent primitive is tested against currently executing primitives in order to detect any dependencies. Accordingly, in our example, primitive 3 will be tested against primitives 1 and 2 for dependencies. Since primitive 3 overlaps primitives 1

and 2, it cannot be executed until primitives 1 and 2 are both complete. Using the out-of-order dispatch unit, if primitive 1 completes before primitive 2, primitive 3 may be bypassed and primitive 4 is then processed/executed. Once primitive 2 completes processing, then primitive 3 may be executed. Accordingly, the out-of-order dispatch system prevents the next primitive in the list from executing until all previous primitives that overlap that primitive have been completed while allowing subsequent primitives which do not overlap to be executed. This allows for parallel processing and execution of primitives while preserving the ordering and integrity of the primitives thereby insuring that the final graphic is properly drawn.

Therefore, utilizing the preferred embodiment of the present invention in which an outof-order dispatch unit is used, although primitive 3 cannot be approved for execution since it
overlaps with the currently executing primitives, in order to extract additional parallelism, it is
preferable to allow out of-of-order dispatch of other primitives in the queue. In this case, stalled
operations or primitives which cannot be executed are placed into central reservation stations
(i.e. primitive 3) and other operations that can proceed independently (i.e. other primitives
which can be processed immediately since there is no overlap) are allowed to bypass them.
Accordingly, if either primitive 1 or 2 completes before the other, primitive 4 can begin
execution, as shown in FIG. 4c.

Dependency Checking

In both embodiments (i.e. using either an in-order or an out-of-order dispatch mechanism), all incoming primitives are placed in reservation stations and the oldest eligible candidate (i.e., the oldest primitive eligible for execution which has no dependencies) is dispatched each cycle as an accelerator / rasterizer becomes available. Accordingly, in both

embodiments, it is necessary to have a mechanism for checking the dependency of each incoming primitive against each primitive currently being processed by one of the accelerator/rasterizer. The preferred embodiment which uses an in-order dispatch unit will only allow primitives to be executed concurrently in order so long as no dependencies exist. The preferred embodiment which uses an out-of-order dispatch unit is able to bypass primitives which are dependent and execute the next oldest eligible candidate in the queue. Each of these embodiments will be described in greater detail; but, first, the mechanism for checking dependencies is similar in both the in-order and out-of-order systems and will be described herein.

In order to implement parallel processing and execution of primitives, mechanisms are required for detecting dependences, for detecting ready operations, and for tracking completion of operations. In a preferred embodiment, dependence checking is accomplished by comparing the source and destination register addresses of a candidate operation yet to be processed/executed with those of previous operations in the sequential instruction stream which are being currently processed/executed. If a corollary exists for graphics primitives they are said to be dependent.

More specifically, any given graphics primitive has a set of destination pixel locations where it will, upon completion of the operation, draw the graphics. The graphics primitive will also have one or more sets of source pixels which are read for performing the drawing operation. The destination pixels are the ones drawn by the rasterization operation and the source pixels may include the old pixels in those locations that will be alpha-blended and texture mapped in order to draw the triangle.

In the present invention, using a unique algorithm for detecting dependences, every dispatched primitive reserves a region of the frame buffer corresponding to a bounding box surrounding each of its operands. The sets of pixel locations that each primitive reads in order to complete its drawing operation are called its source operands and bounding boxes surrounding each of the source operands are called the source regions. The set of pixel locations where each primitive will draw its graphics upon completion is called its destination operand and a bounding box around it is the destination region. Bounding boxes are preferably computed by taking the minimum and maximum values of the x and y coordinates of each vertex for the box, which must be large enough to include all the destination or source pixel locations.

Graphics primitives can have several source regions as well as a destination region; but, for simplicity, consider the case where there is one of each. In this case, a previously dispatched and currently processing/executing primitive D will have a set of source pixel locations or a source operand surrounded by a bounding box and a set of destination pixel locations or a destination operand which is also surrounding by a bounding box. A candidate or new primitive which has yet to be processed/executed P will also have a set of source pixel locations or a source operand surrounded by a bounding box and a set of destination pixel locations or a destination operand which is also surrounding by a bounding box. In a preferred embodiment, in order to determine whether or not the candidate primitive P depends on the previously dispatched primitive D, the function depend(P,D) is computed. Now, if SP is the source region of P and DP is the destination region of P and, furthermore, SD and DD are the

source and destination regions of D, the dependency between the two can be determined by the following equation:

$$depend(P,D) = (S_P \cap D_D) + (D_P \cap D_D) + (D_P \cap S_D)$$

If depend(P,D) is false then P can be dispatched concurrently with D. Dependency is said to be false for any two concurrently dispatched primitives even if their source regions overlap, so long as neither source region for either primitive overlaps with the destination region of the other primitive and so long as the destination regions of the two primitives do not overlap.

In accordance with the equation given above, in order to determine dependency, three tests are performed. The first test prevents any read after write (RAW) hazards caused by reading a source pixel prior to it being written by the earlier primitive. The second test prevents any write after write (WAW) hazards caused by writing a pixel from the second primitive prior to writing the same pixel from the first primitive. The third test prevents any write after read (WAR) hazards caused by writing a pixel from the second primitive prior to reading the same pixel for the first primitive. The WAR hazard is somewhat unique in that it would be prevented in any well constructed processor pipeline by reading the source operands of the first instruction from the register file early in the pipeline and retaining a copy of the correct value until it is actually used in the pipeline. However, it is sometimes impractical to copy the values of all of the source pixels for a graphics primitive, so the source region in a preferred embodiment is reserved in memory until an operation completes, and the WAR test is performed against any subsequently issuing primitives.

FIG 5 illustrates a preferred embodiment of the present invention which utilizes either an in-order dispatch mechanism or an out of order dispatch mechanism for providing graphics primitives to a plurality of graphics accelerators/rasterizers. As shown, the preferred embodiment of the present invention is comprised of a fetch unit 510, an issue unit 520, a bus line 530, several parallel 3D graphics accelerators/rasterizers 540a-n, and a memory interface unit 550. The fetch unit 510 includes a command queue 512 which contains all of the graphics primitives to be processed and displayed in a single frame. The issue unit 520 includes reservation stations 522a-n and candidate buffers 524a-n. As reservation stations 522a-n in the issue unit 520 become available, primitives are passed from the command queue 512 to the reservation stations 522a-n in the issue unit 520 for dependence testing and scheduling.

In a preferred embodiment, the issue unit 520 can issue one primitive per cycle to any one of the several graphics accelerators/rasterizers 540a-n for rasterization. As each primitive is completed, the graphics accelerator/rasterizer 540a-n executing that primitive then notifies the issue unit 520 so that the primitive can be retired and the reservation stations 522a-n associated with that primitive can be cleared. The graphics accelerators 540a-n access a memory (not shown) through a global memory interface unit 550. In a preferred embodiment, the memory interface unit 550 may be comprised of a large switch with many independent memory banks to provide adequate bandwidth with the memory comprising a single I/O ported memory array such that the memory interface unit 550 may retrieve information from any address in the array and buffer the information in any one of the memory banks.

In a preferred embodiment, the reservation stations 522a-n each use three sets of registers to store data about pending and executing primitives. A first set of registers are

known as the destination reservation stations which hold bounding box coordinates which identify the destination region for each new primitive as it is passed from the command queue 512 in the fetch unit 510 to the reservation stations 522a-n in the issue unit 520. For simplicity in understanding the invention, in this example it is assumed that every primitive has exactly one destination region and the coordinates for the bounding box for that destination region is stored in the destination reservation station. It is understood that in alternative embodiments, a primitive may have more than one destination region, in which case dependencies between any two primitives will have to be resolved for each destination region before the primitive having more than one destination region can be executed.

It is understood that in the preferred embodiment, a primitive may also have zero, one, or two source regions. Accordingly, a second set of registers known as the source reservation stations are used to store bounding box coordinates which identify source regions for each of the primitives passed from the command queue 512 in the fetch unit 510 to the reservation stations 552a-n in the issue unit 520. Each source reservation station contains a bounding box descriptor or coordinates for each source region and a tag that is used as an address index between the source reservation station and the corresponding destination reservation stations where the corresponding destination region which uses that source region is stored. For example, it is assumed there is one destination region for primitive 1 and that destination region is stored in a destination reservation station. Let us further assume that primitive one has two different source regions. Bounding box coordinates for each source region associated with primitive 1 are stored in the source reservation stations along with tags which identify the addresses location in the destination reservation stations where the corresponding destination region coordinates are stored.

Finally, the candidate buffers 524a-n each hold relevant information about unissued primitives. Unissued primitives are those which have not yet been sent to a graphics accelerator/rasterizer for processing.540a-n. This relevant information includes the opcode and additional operands for the primitive (such as vertex colors, alpha values, etc.) and a dependence vector that describes any restrictions on issuing the primitive. Alternatively, a pointer to the opcode and operand can be included rather than the actual data and the data can be stored in a memory and accessed via the memory interface unit 550 once the primitive is passed to one of the accelerators/rasterizers 540a-n for processing. Once again, in a preferred embodiment, the candidate buffers include a tag which is used to specify the address of the location in the destination reservation station index where the bounding box coordinates of the destination region for that primitive are stored.

In a preferred embodiment, every entry in the source and destination reservation stations and every entry in the candidate buffers has a valid bit that is used to indicate whether that entry contains live data or not. Ideally, the number of destination reservation stations should equal the number of candidate buffers plus the number of accelerators/rasterizers 540ann such that there are a sufficient number of destination reservation stations to store bounding box coordinates for those primitives being executed and those yet to be executed in the queue.

FIG. 6a illustrates the process executed when processing graphics primitives and using an in order dispatch mechanism in accordance with a preferred embodiment of the present invention. First, a plurality of primitives are moved into the issue unit from the fetch unit, one primitive being moved each clock cycle provided that there is an empty destination reservation station, an empty candidate buffer, and enough empty source reservation stations to hold all the

source regions used by that primitive STEP 601. In a preferred embodiment, hardware, firmware or software resident in the fetch unit has already decoded the primitive type and computed the bounding box coordinates for each source and destination region. When the primitive is moved from the issue unit into the fetch unit, the coordinates for the bounding boxes are stored in the source and destination reservation stations, accordingly, and the address index of the location of the destination region in the destination reservation station is stored in the tag field of the source reservation stations and the candidate buffer STEP 602.

Once every candidate buffer entry is full, the primitives stored in the buffer can begin executing. Thus, in an embodiment which utilizes an in-order dispatch unit, the primitives in the candidate buffer can begin executing in order. Before each primitive is passed to an available accelerator/rasterizer, a dependence vector is computed for that primitive STEP 603. It is obvious that for the first primitive in the candidate buffer there should be no dependency conflicts. After that, the dependencies between each subsequent primitive and any currently processing or executing primitives are determined. Dependencies are computed for single source and single destination primitives in accordance with the dependent function equation provided earlier. If any one primitive has more then one source region, a variation of the depend function equation is used to compute dependency for each of the two source regions of the primitive. For example, if each primitive has 2 source regions then the dependency function would be as follows:

$$depend(P,D) = (S_{P0} \cap D_D) + (S_{P1} \cap D_D) + (D_P \cap D_D) + (D_P \cap S_{D0}) + (D_P \cap S_{D1})$$

If there is no dependency conflict, the primitive is then passed to one of the available graphics accelerators/rasterizers 540a-n STEP 604. If there is a conflict, the primitive is not passed to the next available graphics accelerator/rasterizer 540a-n. Instead, the system will await until the primitive which is currently executing and causing the dependency in completed and then the next primitive will be passed to an available accelerator/rasterizer STEP 605. Remember, this is a preferred embodiment in which an in-order dispatch unit is used and, therefore, it is not possible to execute the primitives out of order.

Once all of the accelerators/rasterizers 540a-n are loaded (assuming they can all be loaded since if no dependencies are detected), no more primitives can be passed until at least one of the accelerators/rasterizers becomes available. When a graphics accelerator/rasterizer completes executing a primitive, the entries in the source and destination reservation stations for that primitive are cleared, as well as the entry in the candidate buffer STEP 606. The candidate buffer in the issue unit which was holding the information for that now completed primitive is now available and a new primitive can then be passed from the fetch unit to the issue unit STEP 607 in accordance with the explanation provided above. Furthermore, whenever any graphics accelerator/rasterizer is not busy executing a primitive, the candidate buffer is searched for the next primitive in the list STEP 607. Accordingly, as each primitive completes execution, the candidate buffer is searched for the oldest entry. The oldest primitive in the candidate buffer then has its dependency calculated once again to ensure there are no conflicts. If there are conflicts then the in-order dispatch mechanism will not pass the next primitive to the available accelerator/rasterizer; but, will wait for the currently executing primitive which is causing the dependency to complete execution before executing the next primitive in the candidate buffer.

FIG. 6b illustrates the process executed when processing graphics primitives and using an out-of-order dispatch unit in accordance with a second preferred embodiment of the present invention. A plurality of primitives are first moved into the issue unit from the fetch unit, one primitive being moved each clock cycle provided that there is an empty destination reservation station, an empty candidate buffer, and enough empty source reservation stations to hold all the source regions used by that primitive STEP 610. In a preferred embodiment, hardware, firmware or software resident in the fetch unit has already decoded the primitive type and computed the bounding box coordinates for each source and destination region. When the primitive is moved from the issue unit into the fetch unit, the coordinates for the bounding boxes are stored in the source and destination reservation stations, accordingly, and the address index of the location of the destination region in the destination reservation station is stored in the tag field of the source reservation stations and the candidate buffer STEP 615.

Once the candidate buffer is full, the primitives stored in the buffer can begin executing. Thus, for each primitive in the candidate buffer, a dependence vector is computed STEP 620. It is obvious that for the first primitive in the candidate buffer there should be no dependency conflicts. After that, the dependencies between each subsequent primitive and any currently processing or executing primitives are determined.

If any one primitive has more then one source region, a variation of the depend function is used to compute dependency for each of the two source regions of the primitive as shown above. If there is no dependency conflict, the primitive is then passed to one of the available graphics accelerators/rasterizers 540a-n STEP 625. If there is a conflict, the primitive is not

passed to the next available graphics accelerator/rasterizer 540a-n. Instead, since this embodiment utilizes an out-of-order dispatch mechanism, that primitive will be bypassed and the next primitive in the candidate buffer will have its dependency computed STEP 630.

Once all of the accelerators/rasterizers 540a-n are loaded, no more primitives can be passed until at least one of the accelerators/rasterizers becomes available. When a graphics accelerator/rasterizer completes executing a primitive, the entries in the source and destination reservation stations for that primitive are cleared, as well as the entry in the candidate buffer STEP 635. A new primitive can then be passed from the fetch unit to the issue unit in accordance with the explanation provided above STEP 640. Furthermore, when a graphics accelerator/rasterizer completes executing a primitive, the candidate buffer is searched for the next oldest and eligible primitive STEP 640. In this embodiment which uses an out of order dispatch unit, the next oldest and eligible primitive is defined as that primitive in the candidate buffer which is the oldest and which has no dependency conflicts. Accordingly, as each primitive is executed, a new primitive is loaded into the issue unit and the candidate buffer is searched for the oldest entry. The oldest primitive in the candidate buffer then has its dependency calculated once again to ensure there are no conflicts.

Hardware for Computing Dependencies

A preferred embodiment of the hardware used to compute dependencies is shown in FIG. 7. A shown in FIG. 7, the bounding box coordinates for the destination regions and the source regions of the primitive are driven onto vertical buses for each operand. In the example shown, the primitive has a single destination region 701, and two source regions 702 and 703. Additionally, the bounding box coordinates for the destination regions which are stored in each

valid reservation station are driven onto horizontal bus lines. At the intersections which correspond to potential hazards, bounding box coordinate overlap comparators implement the depend function described earlier. A dependence vector is thus calculated by computing whether or not the destination regions or source regions of the new primitive overlap with the destination regions of each primitive which is currently executing. Bit k in the dependence vector is set if the new primitive must wait for the primitive stored in destination reservation station k to complete, where k is the position in the destination reservation station where the conflicting primitives destination region coordinates are stored - i.e. destination reservation station 1, destination reservation station 2, etc.. This dependence vector is stored in the candidate buffer reserved for the new primitive. At the same time, the issue unit is testing the existing issue candidates to see if any are ready to be issued. If any of the accelerators/rasterizers are available, then the issue unit tests all of the dependence vectors in the candidate buffers. If any valid candidate buffer contains a dependence vector of all zeros, then the primitive in the candidate buffer can be passed to the available graphics accelerator/rasterizer for processing on the next cycle. In a preferred embodiment, if more than one primitive in the candidate buffer has no dependency conflicts that entry which corresponds with the earlier primitive or the primitive which has been in the candidate buffer the longest is the one which is selected for processing. At the next clock cycle, the primitive from the candidate buffer is issued by transferring the primitive data and the tag to the available accelerator and clearing the valid bit in order to free that space up in the candidate buffer so a new primitive can be passed from the fetch unit to the issue unit.

As explained earlier, as the accelerators/rasterizers complete execution and processing of a primitive, the tag corresponding with that primitive is returned to the

issue unit. The issue unit will then clear the valid bit for the entry in the destination reservation station which corresponding with that primitive to free up that space in the destination reservation station. The issue unit will also use the tag corresponding with the completed primitive to clear valid bits in the source reservation stations in order to make these spaces available for other primitives. Finally, the tag is decoded and the corresponding bit in any dependence vectors in the candidate buffer is cleared. This removes all information associated with the completed primitive from the reservation stations and clears any dependencies for pending primitives associated with that primitive. Once all of the dependence bits in a candidate's dependence vector have been cleared, that candidate is then said to be eligible and can then pass to a graphics accelerator/rasterizer on a subsequent clock cycle.

The above description is intended to illustrate the operation of the preferred embodiments of the present invention and is not meant to limit the scope of the invention. The scope of the invention is to be limited only by the following claims. From the above discussion, many variations will be apparent to one skilled in the art that would yet be encompassed by the spirit and scope of the invention.

Claims

What is claimed is:

1. A method for determining dependencies between a first graphics primitive and a second graphics primitive, the method comprising:

calculating a first bounding box for the first graphics primitive; calculating a second bounding box for the second graphics primitive; and determining whether the first bounding box and the second bounding box overlap, wherein a dependency is detected if the boundary boxes overlap.

- 2. The method of claim 1, wherein the first bounding box surrounds a source operand of the first graphics primitive.
- 3. The method of claim 2 wherein the second bounding box surrounds a destination operand of the second graphics primitive.
- 4. The method of claim 3, wherein a write after read dependency is detected if the second bounding box overlaps the first bounding box.
- 5. The method of claim 1, wherein the first bounding box surrounds a destination operand of the first graphics primitive.
- 6. The method of claim 5, wherein a second bounding box surrounds a destination operand of the second graphics primitive.
- 7. The method of claim 6, wherein a write after write dependency is detected if the second bounding box overlaps the first bounding box.
- 8. A method for determining whether a dependency exists between a first graphics primitive and second graphics primitive, comprising:

- comparing locations of pixels to be drawn by the first graphics primitive with locations of pixels to be drawn by the second graphics primitive; and determining whether a dependency exists between the first and second graphics primitives as a function of the comparison of the locations of the pixels to be drawn by each primitive.
- The method of claim 8 wherein the step of comparing is comprised of: calculating a first bounding box which surrounds the pixels to be drawn by the first graphics primitive;
 - calculating a second bounding box which surrounds the pixels to be drawn by the second graphics primitive; and
 - comparing the first bounding box with the second bounding box.
- 10. The method of claim 9, wherein a dependency exists between the first and second graphics primitive if the first and second bounding boxes overlap.
- 11. A method for determining whether a dependency exists between a first graphics primitive and a second graphics primitive, comprising:
 - comparing locations of pixels to be drawn by the first graphics primitive with locations of pixels to be used as source operands by the second graphics primitive; and
 - determining whether a dependency exists between the first and second graphics primitives as a function of the comparison.
- 12. The method of claim 11 wherein the step of comparing is comprised of: calculating a first bounding box which surrounds the pixels to be drawn by the first graphics primitive;
 - calculating a second bounding box which surrounds the pixels to be used as source operands and by the second graphics primitive; and determining whether there is dependfirst and second bounding boxes overlap.

- 13. The process of claim 12, wherein a dependency exists between the first and second graphics primitive if the first and second bounding boxes overlap.
- 14. An apparatus for detecting dependencies between a first graphics primitive and a second graphics primitive, comprising:
 - a destination reservation station for storing a destination bounding box location for the first graphics primitive;
 - a source reservation station for storing a source bounding box location for the first graphics primitive; and
 - a first comparator for comparing the destination bounding box location for the first graphics primitive with the location of pixels to be drawn by the second graphics primitive and generating a first resultant bit.
- 15. The apparatus of claim 14 further comprising:
- a second comparator for comparing the source bounding box location for the first graphics primitive with the location of pixels to be drawn by the second graphics primitive and generating a second resultant bit.
- 16. The apparatus of claim 15 further comprising:
 - a third comparator for comparing the destination bounding box location for the first graphics primitive with the location of source pixels to be used by the second graphics primitive and generating a third resultant bit.
- 17. The apparatus of claim 16, further comprising:
- a logic OR gate for receiving the first, second, and third resultant bits and performing a logical OR operation in order to determine whether any dependencies exist between the first and second graphics primitives.
- 18. A method for parallel processing of a plurality of 3D primitives in an out of order sequence comprising;

storing the plurality of 3D primitives in a queue;

- processing at least two of the primitives in order at the same time, where that at least two of the primitives have no dependency and wherein a first primitive in the at least two is completely processed before the others;
- detecting a dependency between a next primitive to be processed from the plurality in the queue and the primitives in the at least two which have not yet been completely processed; and
- skipping the next primitive to be processed from the plurality in the queue and processing a subsequent primitive from the plurality in the queue, wherein no dependency is detected between the subsequent primitive and the primitives in the at least two which have not yet been completely processed.
- 19. The method of claim 18 where the step of detecting is comprised of:
 comparing destination regions for the primitives in the at least two which have
 not yet been completely processed with a new destination region and
 source regions for the next primitive to be processed in order to detect
 any overlap; and
 - detecting a dependency where there is an overlap between the destination regions for the primitives in the at least two which have not yet completely processed and either the new destination region or the source regions for the next primitive to be processed.
- 20. A method for providing out of order processing of a plurality of 3D primitives comprising;
 - storing the plurality of 3D primitives, including source and destination region bounding box coordinates for each primitive, in an issue unit;
 - processing at least two of the primitives at the same time, where that at least two of the primitives have no dependency; and
 - detecting a dependency between a next primitive to be processed from the plurality in the issue unit and the primitives in the at least two which have not yet been completely processed, wherein the next primitive to be

processed from the plurality in the issue unit is skipped if a dependency is detected.

- 21. The method of claim 20, wherein a subsequent primitive from the plurality in the issue unit is processed if no dependency is detected between the subsequent primitive and the primitives in the at least two which have not yet been completely processed.
- 22. The method of claim 3 wherein the step of detecting is comprised of:

 comparing the destination region bounding box coordinates for the primitives in

 the at least two which have not yet been completely processed with the

 destination region bounding box coordinates and the source region

 bounding box coordinates for the next primitive to be processed in order

 to detect a dependency; and
 - detecting a dependency if there is an overlap in the destination region bounding box coordinates for the primitives in the at least two which have not yet been completely processed and either the destination region bounding box coordinates or the source region bounding box coordinates for the next primitive to be processed.
- 23. An apparatus for providing out of order processing of a plurality of graphics primitives comprising;
 - an issue unit for storing the plurality of graphics primitives including source and destination region bounding box coordinates for each primitive in the plurality;
 - two or more accelerators for processing at least two of the primitives in the plurality at the same time, where the at least two of the primitives have no dependency; and
 - comparators for detecting a dependency between a next primitive to be processed from the plurality in the issue unit and the primitives in the at least two which have not yet been completely processed, wherein the next

primitive to be processed from the plurality in the issue unit is skipped if a dependency is detected.

- 24. The apparatus of claim 23, wherein a subsequent primitive from the plurality in the issue unit is processed if no dependency is detected between the subsequent primitive and the primitives in the at least two which have not yet been completely processed.
- 25. The apparatus of claim 23 wherein the issue unit includes:
 source reservation stations for storing the source region bounding box
 coordinates for each primitive in the plurality stored in the issue unit; and
 destination reservation stations for storing the destination region bounding box
 coordinates for each primitive in the plurality stored in the issue unit.
- 26. The apparatus of claim 25 wherein the comparators compare the destination region bounding box coordinates for the primitives in the at least two which have not yet been completely processed with the destination region bounding box coordinates and the source region bounding box coordinates for the next primitive to be processed in order to detect a dependency.
- 27. The apparatus of claim 26 wherein a dependency is detected if there is an overlap in the destination region bounding box coordinates for the primitives in the at least two which have not yet been completely processed and either the destination region bounding box coordinates or the source region bounding box coordinates for the next primitive to be processed.

ABSTRACT OF THE DISCLOSURE

A method, apparatus and computer program product for parallel execution of primitives in 3D graphics engines. It includes detection and preservation of dependences between graphics primitives with the ability to execute multiple independent primitives concurrently while preserving their ordering because the architecture of the graphics engine for the present invention further provides concurrent resources for parallel execution. In a first preferred embodiment, primitives are executed in parallel using an in-order dispatch unit capable of detecting dependencies between primitives. In a second preferred embodiment, an out-of-order dispatch unit is used such that not only are primitives executed concurrently; but, the primitives may be executed in any order when dependencies are detected.




Figure 1




Figure 2:




FIG. 3a




FIG. 3b




FIG. 4a




FIG. 4b





FIG. 4c






FIG. 6a




FIG. 6b




FIG. 7

Approved for use through 10/31/96 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

2926 US

COMPLETE IF KNOWN

Andrew Wolfe

Attorney Docket Number

First Named Inventor

[] Additional provisional

application numbers are listed on a supplemental sheet attached hereto.

1	OR DESIGN PPLICATION	Application Nu	mber Please a	Please assign November 16, 2000		
		Filing Date	Novemb			
		Group Art Unit	Unknow	n		
[X] Declaration Submitted with Initial Filing	OR [] Declaration Submitted a Initial Filing	Examiner Name	Unknow	n		
As a below named inventor, I he My residence, post office addrest believe I am the original, first plural names are listed below) o	ss, and citizenship are as sta	ne name is listed below) or	an original first and is int	inventor (if		
		RSCALAR 3D GRAPHIC		····		
[X] is attached hereto OR [] was filed on amended on (MM/DD/YYYY) I hereby state that I have review amended by any amendment spe I acknowledge the duty to disclo Regulations. § 1.56.	ed and understand the conte cifically referred to above. se information which is ma	applicable). ents of the above identified	fined in Title 37 Code of F	ederal		
I hereby claim foreign priority be for patent or inventor's certifica States of America, listed below of any PCT international applica	and have also identified bel	international application was low, by checking the box, a fore that of the application	hich designated at least on	e country other the	an the United s certificate, o	
Prior Foreign Application Number(s)	Country	Foreign Filing Date	Priority	Certified Co	py Attached?	
Tvurioci(s)		(MM/DD/YYYY)	Not Claimed	YES	NO	
					[]	
					[]	
			[]		[]	
			i i	1 1	[]	
Additional foreign appli	cation numbers are listed	on a supplemental price	rity sheet attached heret	0.		

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

Filing Date (MM/DD/YYYY)

U.S. Department of Commerce

Patent and Trademark Office

DECLARATION FOR

Application Number(s)

0010/PTO

Rev. 6/95

	DECI	LARATIO	V			Page 2						
claims of this the first parag patentability	hereby claim the benefit under Title 35, United States Code § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the portion application and the national or PCT international filing date of this application.											
U.S. Paren	t Application mber	PCT F	PCT Parent Parent Filing Date Parent Patent Number									
INU	nioei	Nun	nber	per (MM/DD/YYYY) (if a				(if appli	icable)	•		
[] Addition	al U.S. or PCT in	ternational appl	ication nun	nbers are	listed or	n a sı	ppleme	ental p	riority sh	neet attached	d hereto.	
As a named in	e Patent and Trad	appoint the follo	owing attorn	nev(s) an								all
	Name	emark Office co	Registra Numb	ation oer				Name	<u> </u>		Registi Num	
	Greg T. Sueoka Martin S.C. Loui	i	33,80 43,41				John	n R. C	arr	;	42,3	90
Addition Please direct all	[] Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto. Please direct all correspondence to: John R. Carr Fenwick & West LLP Two Palo Alto Square Palo Alto, CA 94306 U.S.A.											
	(415) 875-2431					ax		281-				
are punishable l statements may	e that all statement be true; and further by fine or imprison jeopardize the vali le or First Inv	ment, or both, u idity of the appli	nder Section cation or an	made with	n the kno Title 18 ssued the	owled of the ereon	ge that ve United	willful I States	false stat Code an	ements and d that such	tha 1:1	
Given	lrew	N	Middle nitial	F	Family Name	Wo					Suffix	
Inventor's Signature						<u> </u>		Date			e.g. Jr.	
Residence: Cit	ty		State		Count	ry			C	Citizenship		
Mailing Addre	SS			•							_1	
Mailing Addre	SS								1111			
City			State		Zip				Country			

Additional inventors are being named on supplemental sheet(s) attached hereto